PATENT ABSTRACTS OF JAPAN

(11)Publication number:

03-000790

(43)Date of publication of application: 07.01.1991

(51)Int.CI.

CO9K 11/06

H01L 33/00 H05B 33/14

(21)Application number: 01-142656

(71)Applicant: RICOH CO LTD

(22)Date of filing:

05.06.1989

(72)Inventor: SAITO SHOGO

TSUTSUI TETSUO

ADACHI CHIHAO

(30)Priority

Priority number: 64 30832

Priority date: 08.02.1989

Priority country: JP

(54) ELECTROLUMINESCENT ELEMENT

PURPOSE: To obtain an electroluminescent element which can be manufactured simply, emits light with high luminance, and has excellent durability by using as a luminescent layer a thin film formed by the wet thin-film method from a mixture of an organic compound having a hole-transfer capability and a fluorescent organic compound.

CONSTITUTION: An electroluminescent element provided with a luminescent layer comprising a thin film of an organic substance between two electrodes, wherein the luminescent layer comprises a thin film formed by the wet thin-film method from a mixture of an electron donating organic compound having a hole-transfer capability (e.g. a high-molecular compound, such as polyvinylcarbazol, or a low-molecular compound, such as a compound of formula I or II) and a fluorescent organic compound having an electron-transfer capability (e.g. a compound of formula III or IV). This technique can give an electroluminescent element which can be manufactured simply, emits light with high luminance, and has such excellent durability that the luminous performance is maintained over a long period of time.

LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office